4.2 Periodic Inspection

6LYA-6LY2

Daily and periodic inspection are important to keep the engine in its best condition.

The following is a summary of inspection and servicing items by inspection interval.

Periodic inspection intervals should vary depending on the uses, loads, fuels and lube oils used and handling conditions, and are hard to establish definitively. The following should be treated only as a general standard.

[NOTICE]

Schedule your own periodic inspection plan according to the operational conditions of your engine and inspect every item. Neglect of periodic inspection may lead to engine troubles and shorten the life of the engine. Inspection and servicing at 2000 hours of operation and thereafter require special knowledge and techniques.

Consult your dealer or distributor or the Yanmar subsidiary in your region.

Preiodical Inspection and Maintenance.

Consult	nearest deale
○ : Check	

	-									
Item	Description	Schedule								
		Daily	Every 50 service hrs.	Every 250 service hrs. (or 1 yr.)	Every 500 service hrs. (or 2 yrs.)	Every 1000 service hrs. (or 4 yrs.)	Every 2000 service hrs.	Page		
	Check of fuel leve	el	\circ						20	
Fuel	Draining of tank			0					37	
	Drain of filter and separator	water		0					37 39	
	Replacement of f	ilter element			0				41	
Engine lube oil	Check oil level in add if necessary	oil pan,	0						21	
	Replacement of f	ilter element		(1st time)	0				36	
	Cleaning of lube	oil cooler						•	44	
	Change of lube oil	Engine side		(1st time)	0				36	
	Check of cooling	water discharge	0						29	
Cooling water seawater side)	Check and replace impeller	ement of					0	•	43	
	Cleaning of seaw (including fresh water	ater system r and lube oil cooler)					0	•	44	
	Replacement of a	anti-corrosive zinc			0				42	
Cooling water (fresh water side)	Check and supply level	of fresh water	0						26	
	Replacement of f	resh water			0				43	
	Cleaning of fresh (including heat ex	water system schanger tank)						•	44	

Item	Description	Schedule						
		Daily	Every 50 service hrs.	Every 250 service hrs. (or 1 yr.)	Every 500 service hrs. (or 2 yrs.)	Every 1000 service hrs. (or 4 yrs.)	Every 2000 service hrs.	Page
Fuel injection pump and fuel injection valve	Adiustment of injection timing						•	45
	Overhaul and check of fuel feed pump						•	45
	Adiustment of injection pressure and atomizing condition			(1st time)		•		44
Cylinder head	Adjustment of clearance intake and exhaust valve			(1st time)		•		44
	Lapping the intake/exhaust valve						•	45
Check and adjustment of remote control cable		0		0				39 40
Electrical parts	Check of alarm devices	0						14
	Check of battery electolyte volume		0					38
	Adjustment of alternator(generator) drive belt tension				0			43
Turbo charger	Cleaning of blower			0				40
Marine gear(Yanmar marine gear)	Check and cleaning of lube oil cooler						•	44
	Check and cleaning of lube oil inlet filter net		(1st time)	(2nd time)		0		37
	Check of bearings, friction plate, and seal						•	44
	Check of lube oil level	0						27
	Replacement of lube oil		(1st time)	(2nd time)		0		27
General	Chack for leakage of C.W., L.O., F,O. and exh. gas (inclusing mixing elbow)	0						28